## FHO No.47187 BOOK 24 PACE CERTIFICATE OF LOCATION OF LODE MINING CLAIM PAGE.

(GROUP OF CLAIMS)

dining Claim was loose	S IS TO CERTIFY that the Sum # Lode
lay of March	ed by B.K. Seeley Jr. on the
istrict, Euroka	19.68, in the Fureka Mining County, State of Mevada, further uateds in portions of Sec. 3. 9. 10. 11. 14.
escribed as being situ	sateds in portions of Sec's. 3. 9. 10. 11. 14.
<u> 15. 22. 23 - 1</u>	.201 - R.52E. MDB & M
	<del></del>
	•
The	general course of said lode or vein is northwest.
nd the undersigned cla	ims 10 feet in a Westerly direction
nd <u>1490</u> feet in an	sims 10 feet in a westerly direction of 200 feet on each side of the center of
he vein or lode along	the entire length of said claim.
	end endire langen of said Glaim,
The	location work was done upon the Sun # 5
idim(s) for the benefi	t of a contiguous group of not more than ten (10)
sue mining Claims, the	apecific names of which are as follows:
	11-30-33-31-31-31-4
The	location work done consisted of: Drilling
·	
sting a total of \$ 10	000.00 , of which \$100.00 is applicable to
is claim.	, as made to appear to
nis claim.	, and the second
nis claim.	
nis claim. The	corners and side centers of the claim are located
The nd marked as follows:	corners and side centers of the claim are located  Beginning at the <u>VE</u> corner, marked <u>NE cor</u> Market of 600 feet to the southeast
The dam arked as follows: hence bearing southeas; orner, marked SE go	corners and side centers of the claim are located  Beginning at the <u>NE</u> corner, marked <u>NE</u> cor ;  a distance of 600 feet to the <u>southwest</u> ;  thence bearing southwest a distance
The id marked as follows: ence bearing southeas; orner, marked SE go	corners and side centers of the claim are located Beginning at the <u>NE</u> corner, marked <u>NE</u> cor ;  a distance of 600 feet to the <u>southwest</u> a distance  Bouth side center marked SSC; thence
The ad marked as follows: sence hearing southeas; orner, marked SE gos feet to the earing SU a dista	corners and side centers of the claim are located Beginning at the NE corner, marked NE cor ;  p distance of 600 feet to the southeast  ; thence bearing southwest a distance  south side center , marked SSC ; thence ince of 750 feet to the southwest
The id marked as follows: sence hearing southeas; orner, marked SF gorest to the laring SH a dista	corners and side centers of the claim are located Beginning at the <u>VE</u> corner, marked <u>NE cor</u> ;  p distance of 600 feet to the <u>southwest</u> ; thence bearing anythwest a distance anouth side center, marked <u>SSC</u> ; thence ance of 750 feet to the <u>southwest</u> Stor ; thence bearing northwest a
The id marked as follows: sence hearing southeas; orner, marked SF gorest to the laring SH a dista	corners and side centers of the claim are located Beginning at the <u>VE</u> corner, marked <u>NE cor</u> ;  p distance of 600 feet to the <u>southwest</u> ; thence bearing anythwest a distance anouth side center, marked <u>SSC</u> ; thence ance of 750 feet to the <u>southwest</u> Stor ; thence bearing northwest a
The damarked as follows: sence hearing southeas former, marked SF and feet to the saring SF a distance of 600 feet former.	corners and side centers of the claim are located Beginning at the <u>VE</u> corner, marked <u>NE cor</u> ;  p distance of 600 feet to the <u>southwest</u> ;  thence bearing <u>southwest</u> a distance  south side center , marked <u>SSC</u> ; thence ance of 750 feet to the <u>southwest</u> ;  thence bearing northwest a  set to the <u>northwest corner</u> , marked thence bearing northeast a distance of 750 feet
The d marked as follows: lence hearing southeas former, marked SE go feet to the aring SW a dista corner, marked stance of 600 fe the north side center aring NE a distance of a distance of stance	corners and side centers of the claim are located Beginning at the <u>VE</u> corner, marked <u>NF cor</u> ;  adistance of 600 feet to the <u>southwast</u> ; thence bearing <u>southwest</u> a distance  aouth side center , marked <u>SSC</u> ; thence ince of 750 feet to the <u>southwest</u> Si cor ; thence bearing northwest a northwest corner , marked thence bearing northeast a distance of 750 feet er , marked <u>NSC</u> ; thence istance of 750 feet to the point of beginning.
The d marked as follows: lence bearing southeas former, marked SE go feet to the laring SM a distance of 600 feet former, marked stance of 600 feet former a distance of 600 feet former a	corners and side centers of the claim are located Beginning at the <u>VE</u> corner, marked <u>NF cor</u> ;  adistance of 600 feet to the <u>southwast</u> ; thence bearing <u>southwest</u> a distance  South side center , marked <u>SSC</u> ; thence ince of 750 feet to the <u>southwest</u> set to the <u>northwest dorner</u> , marked thence bearing <u>northwest</u> a distance of 750 feet  thence bearing <u>northwest</u> a distance of 750 feet  or , marked <u>NSC</u> ; thence  stance of 750 feet to the point of beginning.
The d marked as follows: lence bearing southeas former, marked SE go feet to the laring SM a distance of 600 feet former, marked stance of 600 feet former a distance of 600 feet former a	corners and side centers of the claim are located Beginning at the <u>VE</u> corner, marked <u>NF cor</u> ;  adistance of 600 feet to the <u>southwast</u> ; thence bearing <u>southwest</u> a distance  aouth side center , marked <u>SSC</u> ; thence ince of 750 feet to the <u>southwest</u> Si cor ; thence bearing northwest a northwest corner , marked thence bearing northeast a distance of 750 feet er , marked <u>NSC</u> ; thence istance of 750 feet to the point of beginning.
The d marked as follows: lence bearing southeas former, marked SE go feet to the laring SM a distance of 600 feet former, marked stance of 600 feet former a distance of 600 feet former a	corners and side centers of the claim are located Beginning at the <u>VE</u> corner, marked <u>NF cor</u> ;  adistance of 600 feet to the <u>southwast</u> ; thence bearing <u>southwest</u> a distance  South side center , marked <u>SSC</u> ; thence ince of 750 feet to the <u>southwest</u> set to the <u>northwest dorner</u> , marked thence bearing <u>northwest</u> a distance of 750 feet  thence bearing <u>northwest</u> a distance of 750 feet  or , marked <u>NSC</u> ; thence  stance of 750 feet to the point of beginning.
The ad marked as follows: sence hearing southeas orner, marked SE go 750 feet to the aring SM a dista corner, marked stance of 600 fe NW cor , the north side center aring NE a disch of the above descr	corners and side centers of the claim are located Beginning at the NE corner, marked NE cor ;  a distance of 600 feet to the southeast  ; thence bearing southwest a distance  south side center , marked SSC ; thence ince of 750 feet to the southwest  set to the northwest corner , marked thence bearing northwest a distance of 750 feet  or , marked NSC ; thence stance of 750 feet to the point of beginning.  ibed corners is a Rock manument or  a 4 x 4 x 4 post.
The ad marked as follows: sence bearing southeas orner, marked SE go aring SW a dista sorner, marked stance of 600 fe who corner the north side centers of the above description.	corners and side centers of the claim are located Beginning at the NE corner, marked NE cor ;  a distance of 600 feet to the southeast  ; thence bearing southwest a distance  south side center , marked SSC ; thence ince of 750 feet to the southwest  set to the northwest corner , marked thence bearing northwest a distance of 750 feet  or , marked NSC ; thence stance of 750 feet to the point of beginning.  sibed corners is a Rock manument or  a 4 x 4 x 4 post.  location and discovery work referred to above in
The ad marked as follows: sence bearing southeas orner, marked SE go 750 feet to the aring SM a dista sorner, marked stance of 600 fe who cor the north side center aring NE a disch of the above describes to the second of the s	corners and side centers of the claim are located Beginning at the NE corner, marked NE cor ;  a distance of 600 feet to the southeast  ; thence bearing southwest a distance  south side center , marked SSC ; thence ince of 750 feet to the southwest  set to the northwest corner , marked thence bearing northwest a distance of 750 feet  or , marked NSC ; thence stance of 750 feet to the point of beginning.  ibed corners is a Rock manument or  a 4 x 4 x 4 post.
The ad marked as follows: sence bearing southeas orner, marked SE go 750 feet to the aring SM a dista sorner, marked stance of 600 fe who cor the north side center aring NE a disch of the above describes to the second of the s	corners and side centers of the claim are located Beginning at the NE corner, marked NE cor ;  a distance of 600 feet to the southeast  ; thence bearing southwest a distance  south side center , marked SSC ; thence ince of 750 feet to the southwest  St cor ; thence bearing northwest a  met to the northwest corner , marked thence bearing northwest a distance of 750 feet  er , marked NSC ; thence stance of 750 feet to the point of beginning.  The corners is a Rock manument or  a 4 x 4 x 4 post.  location and discovery work referred to above in  the was performed on or before
The ad marked as follows: sence bearing southeas orner, marked SE go a dista sorner, marked stance of 600 fe who for the north side center aring NE a distance of the above description of the above description of the stance of the stanc	corners and side centers of the claim are located  Beginning at the NE corner, marked NE cor ;  a distance of 600 feet to the southeast  ; thence bearing southwest a distance  Bouth side center , marked SSC ; thence  Ince of 750 feet to the southwest  Si cor ; thence bearing northwest a  met to the northwest corner , marked  thence bearing northwest a distance of 750 feet  er , marked NSC ; thence  stance of 750 feet to the point of beginning.  Thence it is a Rock manument or  a 4 x 4 x 4 post.  location and discovery work referred to above in  the was performed on or before  by or on behalf of the undersigned locator(s).
The d marked as follows: sence hearing southeas; orner, marked SE on 750 feet to the aring SH a dista dorner, marked stance of 600 feet marked feet of the above described of the above described feet feet feet feet feet feet feet fe	corners and side centers of the claim are located Beginning at the <u>VE</u> corner, marked <u>NE cor</u> ;  distance of 600 feet to the <u>southwast</u> r, thence bearing <u>southwest</u> a distance  South side center marked <u>SSC</u> ; thence ence of 750 feet to the <u>southwest</u> Si cor; thence bearing northwest a northwest gorner marked thence bearing northwast a distance of 750 feet er, marked <u>NSC</u> ; thence et ance of 750 feet to the point of beginning. The sibed corners is a <u>Rock monument or</u> a 4 x 4 x 4 a post.  10cation and discovery work referred to above in the was performed on or before by or on behalf of the undersigned locator(s).
The ad marked as follows: nence hearing southeas orner, marked SE go aring su a dista sorner, marked stance of 600 fe who corner side centers of the north side centers of the above description of the above description of the stance of the above description of the stance of the above description of the stance of the stance of the stance of the above description of the stance of	corners and side centers of the claim are located Beginning at the NE corner, marked NE cor ;  a distance of 600 feet to the southeast r; thence bearing southwest a distance Bouth side center marked SSC; thence ance of 750 feet to the southwest  Si cor ; thence bearing northwest a let to the northwest corner marked thence bearing northwest a distance of 750 feet er marked NSC; thence stance of 750 feet to the point of beginning. The corners is a Rock groupent or a 4 x 4 x 42 post.  location and discovery work referred to above in the was performed on or before by or on behalf of the undersigned locator(s).  1423 F Sth So Salt Lake City High RECORDED AT THE PROPERTY OF SECTION OF THE PROPERTY O
The  Ind marked as follows:  Index bearing southeas  I	corners and side centers of the claim are located Beginning at the NE corner, marked NE cor ;  a distance of 600 feet to the southeast  r ; thence bearing southwest a distance  south side center , marked SSC ; thence ince of 750 feet to the southwest  side cor ; thence bearing northwest a  northwest corner , marked thence bearing northwest a distance of 750 feet  or , marked NSC ; thence stance of 750 feet to the point of beginning.  Thence is a Rock monument or  a 4 x 4 x 4 post.  location and discovery work referred to above in  the was performed on or before by or on behalf of the undersigned locator(s).    1423 F Gth 50 Salt Lake City   Italian
The  Ind marked as follows:  Index bearing southeas  I	corners and side centers of the claim are located Beginning at the NE corner, marked NE cor ;  p distance of 600 feet to the southeast;  r thence bearing southwest a distance Bouth side center , marked SSC ; thence ince of 750 feet to the southwest.  Si cor ; thence bearing northwest a  set to the northwest corner , marked thence bearing northeast a distance of 750 feet er , marked NSC ; thence stance of 750 feet to the point of beginning. sibed corners is a Rock manument or a 4 x 4 x 4 is post.  location and discovery work referred to above in the was performed on or before by or on behalf of the undersigned locator(s).    1423