CERTIFICATE OF LOCATION OF LODE NISTING CIAIN

(GROUP OF CLAIMS)

lining Claim was 1	Taken Per P 1	RTIPY that the am & D.	7 P. 13
av of March	1966 in	the Europa ounty State of Marada, fu portions of Sea's, 1 9	Mining
Matrict Eur	e ka sa sa sa sa sa sa sa C	cunty State of Bounds, fu	rther
escribed as being	situated: ir	portions of Seals 3 9	10. 11. 14.
15, 22, 2	- 7.67	27 (27) (27)	ta ing Mangara sa Kita
		이렇지 종류 강인 바다 없이 속이 제하는	
	The ceneral co	ourse of said lode or vein	is northwest.
nd the undersigned	t claims 10	feet in a Westerly	direction
nd 1490 feet	in an easter	y direction from t	he point of
iscovery, with a w	sidth of 300	feet on each side of the	me center of
ne vein or lode a.	long the entire	e length of said claim.	
	The location	work was done upon the S	un 14575
laim(s) for the be	enefit of a co	ntiquous group of not more	than ten (10)
ode Mining Claims	the specific	1-68-89-70-11	loves
- Jun	09 -00 - 0	1-01-57-70-71	-71-A-
	The location	work done consisted of: D	rilling
	 		/
	<u> </u>		
A SECTION OF THE PROPERTY OF T	# 1000 AD	-4-34-5 c100 00 44 spp	liashla to
	\$ 1000.00	, of which \$100.00 is app	licable to
	\$ 1000.00	, of which \$100.00 is app	licable to
osting a total of his claim.	\$ 1000.00	, of which \$100.00 is app	licable to
his claim.	The corners a	nd side centers of the cla	aim are located
his claim.	The corners a	nd side centers of the cla g at the <u>NE</u> corner, marked	im are located
his claim, nd marked as follo hence bearing sout	The corners a was Beginnin heart distance	nd side centers of the cla g at the <u>NE</u> corner, marked a of 600 feet to the so	im are located NE cor 1
his claim, nd marked as follo hence bearing sout	The corners and the same distance from the same distance from the same same same same same same same sam	nd side centers of the cla g at the <u>NE</u> corner, marked e of 600 feet to the so ce bearing southwest	im are located NE cor
his claim, nd marked as follo hence bearing sout norner, marked 18 f 750 feet to	The corners and bear distance the south aid	nd side centers of the cla g at the <u>NE</u> corner, marked e of 600 feet to the so ce bearing southwest 2 de center , marked 860	im are located NE cor otheast distance , thence
nd marked as follo hence bearing sout normer, marked S f 750 feet to earing SH a	The corners and season distance from the south aid	nd side centers of the cla g at the NE corner, marked e of 600 feet to the so ce bearing southwest le center , marked SEC 50 feet to the southwest	im are located NE cor / utheast distance , thence
nd marked as folloner bearing sout to feet to earing Se a corner , marked istance of 600	The corners and season distance of 75 sect to the	nd side centers of the cla g at the NE corner, marked e of 600 feet to the so ce bearing southwest de center , marked SSC of feet to the southwest , thence bearing nort	ME cor / witheast a distance ; thence
nd marked as followed bearing sout to the corner of the co	The corners and the same distance of 75 in Section the same of the	nd side centers of the cla g at the NE corner, marked e of 600 feet to the so ce bearing anythwest decenter, marked 850 feet to the southwest , thence bearing mark northwest corner	dim are located ME cor Witheast distance thence thwest marked ance of 750 feet
nd marked as follohence bearing sout normer, marked sf feet to earing st a corner, marked istance of 600	The corners and the same distance of 75 in Section the same of the	nd side centers of the cla g at the NE corner, marked e of 600 feet to the so ce bearing anythwest decenter, marked 850 feet to the southwest , thence bearing mark northwest corner	wim are located NE cor utheast distance thence marked ance of 750 feet
nd marked as followed bearing sout to the north side earing NE	The corners and the same distance of Telling the corner of the content of the con	nd side centers of the cla g at the NE corner, marked e of 600 feet to the so ce bearing southwest decenter, marked 850 feet to the southwest thence bearing northwest corner aring northwest corner aring northesst a distance rked NSC	dim are located i NE cor utheast distance ; thence t hwest marked ance of 750 feet ; thence of beginning.
nd marked as followed bearing sout to the north side earing NE	The corners and the sent of th	nd side centers of the cla g at the NE corner, marked e of 600 feet to the so ce bearing nouthwest decenter, marked SSC feet to the southwest thence bearing mark northwest corner aring northesst a distance rked NSC 750 feet to the point of ers is a Rock monument	dim are located i NE cor utheast distance ; thence t hwest marked ance of 750 feet ; thence of beginning.
nd marked as followed bearing sout to carring set to carring set to carring set as corner, marked stance of 600 we sor o the north side caring NE	The corners and the sent of th	nd side centers of the cla g at the NE corner, marked e of 600 feet to the so ce bearing southwest decenter, marked 850 feet to the southwest thence bearing northwest corner aring northwest corner aring northesst a distance rked NSC	dim are located i NE cor representation of 750 feet of beginning.
nd marked as followed bearing sout to carring set to carring set to carring set as corner, marked stance of 600 we sor o the north side caring NE	The corners a pws: Beginning hear distance of 75 is corfeet to the center, made a distance of distance	nd side centers of the cla g at the NE corner, marked e of 600 feet to the so ce bearing southwest la center , marked SSC 50 feet to the southwest , thence bearing nort northwest corner aring northesst a distance rked NSC 750 feet to the point of ers is a Rock monument x 44 post.	nim are located i NE cor utheast distance ; thence thest marked ance of 750 feet ; thence of beginning. or
nd marked as folice hence bearing south a corner, marked so former, marked so former, marked stance of 600 MW sor o the north side earing NE ach of the above of the south side south so for the south side south so for the south side south so for the south side south side south so for the south side south so for the south side south so for the south side south si	The corners a pws: Beginning hear distance of Tell succession of the south aid istance of Tell succession of the corner made a distance of the corner made a	nd side centers of the class at the NE corner, marked so food feet to the so ce bearing southwest la center , marked so feet to the southwest , thence bearing northwest corner aring northesst a distanted NSC 750 feet to the point of the southwest is a Rock monument x 42 post.	nim are located i NE cor utheast distance ; thence thest marked ance of 750 feet ; thence of beginning. or
nd marked as followed bearing south a corner , marked so former , marked so former , marked south a corner , marked stance of 600 MW sor o the north side earing NE ach of the above of the location Cert.	The corners as beginning the south side istance of Test to the south side istance of the south side istance of the south side conter the south side corner	nd side centers of the class at the NE corner, marked so food feet to the so ce bearing southwest le center , marked SSC feet to the southwest , thence bearing northwest corner aring northwest corner aring northwest a distarked NSC 750 feet to the point of the southwest corner are is a Rock monument x 4s post.	wim are located i NE cor witheast distance ; thence thence of 750 feet ; thence of beginning. or
nd marked as folk hence bearing sout normer , marked S f 750 feet to earing Sd a c corner , marked istance of 600 W sor o the north side earing NE ach of the above c	The corners as beginning the south side istance of Test to the south side istance of the south side istance of the south side conter the south side corner	nd side centers of the class at the NE corner, marked so food feet to the so ce bearing southwest la center , marked so feet to the southwest , thence bearing northwest corner aring northesst a distanted NSC 750 feet to the point of the southwest is a Rock monument x 42 post.	wim are located i NE cor witheast distance ; thence thence of 750 feet ; thence of beginning. or
nd marked as folk hence bearing sout normer , marked S f 750 feet to earing Sd a c corner , marked istance of 600 W sor o the north side earing NE ach of the above c	The corners as beginning the south side istance of Test to the south side istance of the south side istance of the south side conter the south side corner	nd side centers of the class at the NE corner, marked so food feet to the so ce bearing southwest le center , marked SSC feet to the southwest , thence bearing northwest corner aring northwest corner aring northwest a distarked NSC 750 feet to the point of the southwest corner are is a Rock monument x 4s post.	wim are located i NE cor witheast distance ; thence thence of 750 feet ; thence of beginning. or
nd marked as followed bearing south a corner, marked so former, marked so former, marked south a corner, marked stance of 600. No sor of the north side earing NE ach of the above corner is tance of the labore corner is tance of the north side earing NE ach of the above corner is tance of the labore corner is tance of the labore corner is tance of the labore corner is tance to the labore corne	The corners a bws: Beginning hear distance of 75 is corfeet to the center, many distance of described corners and istance of the corner at x 4. The location of the center was personable to the center of the corner at x 4.	nd side centers of the class at the NE corner, marked so 600 feet to the so ce bearing northwest at the southwest feet to the southwest feet to the southwest feet to the southwest corner aring northwest corner aring northwest corner aring northwest a distance NSC 750 feet to the point of the sis a Rock monument x 42 post. and discovery work referrent formed on or before behalf of the undersigned	wim are located i NE cor uthessi distance ; thence thess ance of 750 feet ; thence of beginning. or ed to above in d locator(s).
nd marked as folk hence bearing sout normer , marked S f 750 feet to earing Sd a c corner , marked istance of 600 W sor o the north side earing NE ach of the above c	The corners a bws: Beginning hear distance of Tell sor feet to the south side of the south side of the south side corner made a distance of described corner to the location of the location o	nd side centers of the class of the NE corner, marked of 600 feet to the so ce bearing anothwest	dim are located i NE cor utheast distance ; thence the marked ance of 750 feet ; thence of beginning. or ed to above in d locator(s).
nd marked as followed bearing south a corner , marked so former , marked so former , marked south stance of 600 MW sor the north side earing NE ach of the above this Location Certifune 15 , 10 Bak. Seeley	The corners a bws: Beginning hear distance of Tell sor feet to the south side of the south side of the south side corner made a distance of described corner to the location of the location o	nd side centers of the class of the NE corner, marked of 600 feet to the so ce bearing anothwest	dim are located NE cor utheast distance ; thence hwest marked ance of 750 feet ; thence of beginning. or ed to above in d locator(s). t lake City, Wesh K Seeley, Jr nins, post 4 Pop M.
nd marked as followed bearing south a corner , marked so former , marked so former , marked south stance of 600 MW sor the north side earing NE ach of the above this Location Certifune 15 , 10 Bak. Seeley	The corners a bws: Beginning hear distance of Tell sor feet to the south side of the south side of the south side corner made a distance of described corner to the location of the location o	nd side centers of the class at the NE corner, marked of 600 feet to the so ce bearing anothwest	im are located NE cor utheast distance ; thence hwest marked ance of 750 feet ; thence of beginning. or t lake City, Heah K Seeley, Jr. hins, pust 4 P. M. gue 5332 MCORDS
nd marked as follohence bearing south morner, marked sf. 750 feet to earing side a corner, marked stance of 600 MW sor o the north side earing NE ach of the above of the stance of the	The corners and the second of the south aid istance of Tell Second of the center, many a distance of described corner a 4 x 4. The location of the second o	nd side centers of the class of the NE corner, marked of 600 feet to the so ce bearing nouthwest and feet to the southwest feet to the southwest there is a district or ner aring northeast a district or ner aring northeast and istrict or ner is a gook monument or the sis a gook monument or ner is a gook of the undersigned on the gook of official groups, gook 24 of official groups, gook 25 offici	im are located NE cor utheast distance ; thence hwest marked ance of 750 feet ; thence of beginning. or t lake City, Heah K Seeley, Jr. hins, pust 4 P. M. gue 5332 MCOROS
nd marked as followed bearing south a corner , marked so former , marked so former , marked stance of 600 MW sor to the north side earing NE ach of the above this Location Certifune 15 , 10 Bak. Seeley	The corners and the second of the south aid istance of Tell Second of the center, many a distance of described corner a 4 x 4. The location of the second o	nd side centers of the class at the NE corner, marked of 600 feet to the so ce bearing anothwest	wim are located NE cor witheast distance thence thence thence of beginning or d locator(s). t lake City, Wah k Seeley, Jr mins pust 4 P. M. age 533 process