

54508
CORNER RECORD

Filed as required by Statutes of Nevada, 1969, Chapter 366.

Sheet 33 of 43 sheets.

Sec. _____ Twp. 19 N. Range 53 E., Mt. Diablo PM.

County of Eureka, State of Nevada.


See other side of sheet for instructions.

Found 2" IP with Brass Cap, R. 53 E., $\frac{1}{12}|7$, R. 54 E., T. 19 N., M.D.B. & M., U.S.G.L.O., 1935.

Found 2" IP with Brass Cap, R. 53 E., $\frac{T. 20 N., 36}{T. 19 N., 1}|6$, T. 19 N., R. 54 E., M.D.B. & M., U.S.G.L.O., 1927.

Found 2" IP with Brass Cap $\frac{2}{11}|1$, T. 19 N., R. 53 E., M.D.B. & M., U.S.G.L.O., 1935.

Found 2" IP with Brass $\frac{c}{c}|1$, T. 19 N., R. 53 E., M.D.B. & M., U.S.G.L.O., 1935.




SURVEYOR'S CERTIFICATE.

I, Robert W. Millard, Registered Land Surveyor No. L.S. 217 in the State of Nevada do hereby certify that the foregoing is a true, complete and accurate representation of the monument, or monuments, recovered, rehabilitated, restored, re-established or otherwise effected and mentioned in the foregoing Corner Record.

Date survey was completed April 10, 1971

Date Corner Record filed May 28, 1971
at 10:50 A.M.


Registered Land Surveyor.

Accepted for filing on this 28th day of May, 1971
in the office of the County Recorder Eureka County,
State of Nevada.


County Recorder

"Sec. 15. A surveyor shall complete, sign and file or cause to be filed with the County Recorder of the county in which the corner is situated a written record of the establishment or restoration of a public land survey corner. Such a filing shall be made for every public land survey corner and accessory to such corner which established, re-established, monumented, re-monumented, restored, rehabilitated, perpetuated or used as control in any survey. The survey information shall be filed within 30 days after the survey is completed, unless the corner and its accessories are substantially as described in an existing corner record filed in accordance with the provisions of this chapter."

Instructions:

In general, the format of the Corner Record should be patterned after the survey notes as used by the Cadastral Engineers or Surveyors employed by the Bureau of Land Management and by Mineral Surveyors.

1. Report either by sketch or narration, or both, complete information concerning ties to existing monuments presumed authentic.
2. (a) If an acceptable monument was found in a perishable or deteriorated condition describe what was found and state actions taken for the rehabilitation or perpetuation of the monument by the Surveyor making this report.
(b) If a new monument was set in the position occupied by the old monument fully describe the new monument as to material, shape, marking, projection above the surface of the ground, if it does project, distance buried below the ground surface, disposition of the old monument, etc.
3. (a) If no acceptable evidence was found of the original monument or the point where it was presumed to have been set clearly indicate by sketch and narration the procedure followed in re-establishing the corner reported herein.
(b) Clearly describe the monument set to perpetuate the corner as re-established and reported herein and indicate any bearing trees or objects noted in the general vicinity of the new monument.
4. Clearly indicate by sketch and narration the location and nature of all reference monuments or objects which would be useful in the re-identification or recovery or re-establishment of any monument referred to herein.
5. If an acceptable monument has been found with reference monuments, accessories and general surroundings materially differing from information contained in previous Corner Records, clearly report herein the conditions observed in the course of this later survey which materially differ from the original recordation.
6. The definition of survey points in terms of coordinates within the Nevada State Coordinate System will become more positive and satisfactory to the public interest as this system is extended and brought into more general use. All Land Surveyors registered for practice in the State of Nevada are encouraged and urged to make use of the State Coordinate System. It is recommended that all Registered Land Surveyors define public land survey corners by State Coordinates in recordations made as required by Chapter 366 of the 1969 Statutes of Nevada and related statutes.