Field Date 14 October 1984

CERTIFIED LAND CORNER RECORDATION

| DESCR | PTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) |
|--|--|
| Record: 40.00 | North between Sections 21 and 22 for one-quarter corner. Set a charred post in mound with pits as per instructions for |
| 79.81 | ¼ Sec. Cor. I find the ¼ sec. cor. falling 28 lks. W. of my line. It is a stake 2½ ins. diam. by 18 ins. long; lying on the ground on a mound of earth and mkd. ¼. |
| 79.81 | The ½ sec. cor. see below |
| | DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: |
| Set: | Built a mound of stone in tire casing to W. |
| | |
| SKETCH, WITH CO | DURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. |
| Reference: | (May Sketch or Paste Reproduction on Reverse Side.) Book NV, page 41. |
| Record: Continued | I destroy all traces of this cor. and its accessories and re- establish it at the same point as follows: Set an iron post 3 ft. long, I in. diam. 24 ins. in the ground for ½ sec. cor. with brass cap mkd. S 21 ½ S 22 |
| | 1914 dig pits $18x18x12$ ins. N. and S. of post 3 ft. dist. and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W. of cor. |
| Found: | |
| | A 1" black iron pipe with brass cap inscribed as shown AND OR SECTION OF THE SEC |
| 1, Paul N. Scherbe | certify that I have carefully performed or reviewed the work |
| done on the diagrammed o | Signature of Surveyor Registration No. |
| Office of Clerk and Record County of FIREKA This "corner record" was fill on the cross-index plat and | ADA PAUL N. 9 SCHERBEL 2 |
| cc: BLM Cerny | County Official |
| McMahon Allen S. Gordor | Cross Index No T R Mer. T R Mer. |
| | T R Mer. |
| | T R Mer. |
| | T R Mer. |
| | T R Mer. |