96835

Field Date 14 October 1984

## CERTIFIED LAND CORNER RECORDATION

DESCRI	TION OF CORNER EVIDENCE FOUND,	AND ORIGINAL RECORD (If known)
Record:		36N, R49E and Section 19, T36N, o Sections 18 and 19, T36N, R50E and . R49E.
80.00	Set a charred post in mound Cor. to Secs. 13-18-19 as	with pits as per instructions for
Found:	Nothing after extensive sea	\ \
	DESCRIPTION OF MONUMENT AND A	ACCESSORIES ESTABLISHED
•	TO PERPETUATE THE ORIGINAL LOCA	
Set:	A 2" galvanized steel pipe 2 inscribed as shown	28" long (BLM type) with brass cap
		see belo
	/	
SKETCH, WITH CO	JRSE AND DISTANCE TO ADJACENT (May Sketch or Paste Reproduction Book NV, page 40.	CORNER IF DETERMINED IN THIS SURVEY. on on Reverse Side.)
	book htt, page 40.	} <del></del>
Set: Continued	S 6805 8	′ /
	T36N  49E R50E M  S13 S18  S24 S19  1984	
RBE	49E R50E T	
出	S13 S18 5 S24 S19 5	ed position. Built mound of stone in
(P)	1984 tire casi	
SCHERBE!	NVd ON Proration	
	0+00 SW S. 31 T36N, F	50E
	26+17.44 Set W <sub>4</sub> S. 31 52+34.88 Set SW S. 30	~
\ \	78+52.32 Not set. W¼ S. 3 104+68.47 Fd. Chilton RLS 1	O in active mining area 404 monument SW S. 19
	130+87.2 Set Wa S. 19 157+04.64 Set SW S. 18	
	183+22.08 Set W4 S. 18 209+39.52 Set SW S. 7	261+74.40 Set SW S. 6 287+91.84 Set W% S. 6
	235+56.96 Set W <sub>4</sub> S. 7	314+09.28 NW S. 6 T36N, R50E
ı,Paul N. Sc	herbelcertify t rner as reported on this recordation f	hat I have carefully performed or reviewed the work
done on the diagrammed co	rner as reported on this recordanion is	6805
	Signature	of Surveyor PAIII. N. PROGESTRATION No.
ATE OF WYOMING, NEV		SCHERBEL SEL
Office of Clerk and Records  County of EUREKA	r,	Will be common of the state of
7 7	d for record on the $9^{th}$ day of $N_0$	vember at 11:00 4 11:00 19 84, was noted
on the cross-index plat and	is assigned page No.N-25, in book	No. 36-49
cc: Chilton BLM		M. 91. Relolesti County Official
Cerny	Crass I	ndex No T R Mer.
McMahon Allen S. Gordon		T R Mer.
		T R Mer T R Mer.
		T R Mer.
		T R Mer.