96836

Field Date 14 October 1984

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) North between Section 13, T36N, R49E and Section 18, T36N, Record:--R50E for one-quarter corner. Set a charred post in mound with pits as per instructions for 40.00 ⅓ Sec. Cor. Found: --Nothing after extensive search. DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: A 2" galvanized steel pipe 28" long (BLM type) with brass cap Set:-inscribed as shown see below SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) Reference: --Book NV, page 40. RLS 6805 Set:--8/0 Continued R50E HERB/ R49E \$13 S19 at restored position with a mound of stone T36N in tire casing to W. 1984 N JURA Proration T36N, R50E 0+00 SW S. 31 Set W¼ S. Set SW S. 26+17.44 31 30 52+34.88 78+52.32 Not set. Wa S. 30 in active mining area Fd. Chilton RLS 1404 monument SW S. 19 104+68.47 130+87.2 Set W¼ S. 19 Set SW S. 18 157+04.64 183+22.08 Set W¼ S. 18 261+74.40 Set SW S. 6 Set SW S. 7 287+91.84 Set W¼ S. 6 209+39.52 314+09.28 NW S. 6 T36N, R50E Set Wa S. 7 235+56.96 Paul N. Scherbel done on the diagrammed corner as reported on this recordation form and appropriate same conditions. 6805 Signature of Surveyo Registration No. PAUL N. SCHERBEL .. ATE OF WAYOMING, NEVADA Office of Clerk and Recorder, County of... No. 6805 This "corner record" was filed for record on the $q^{\frac{\pi t_2}{2}}$ This "corner record" was filed for record on the $\frac{q^{\frac{15}{2}}}{2}$ day of November at on the cross-index plat and is assigned page No. $\frac{L-25}{2}$, in book No. $\frac{36-4}{2}$ M. M. Reboleati Chilton cc: County Official BLM Cerny Cross Index No. McMahon Allen S. Gordon . R. __ . T. _ _ R. __ _, R. _, _ R. ____