

25 October 1984

T36N, R49E

96838

Field Date
14 October 1984

CERTIFIED LAND CORNER RECORDATION


DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)
Record:-- North between Section 12, T36N, R49E and Section 7, T36N, R50E for one-quarter corner.
40.00 Set a charred post in mound with pits as per instructions for $\frac{1}{4}$ Sec. Cor.
Found:-- Nothing after intensive search.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:
Set:-- A 2" galvanized steel pipe 28" long (BLM type) with brass cap inscribed as shown

see below

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)
Reference:-- Book NV, page 40.

Set:--
Continued



at restored position with a mound of stone in tire casing to W.

Proration

0+00	SW S. 31	T36N, R50E	
26+17.44	Set $W\frac{1}{4}$ S. 31		
52+34.88	Set SW S. 30		
78+52.32	Not set. $W\frac{1}{4}$ S. 30 in active mining area		
104+68.47	Fd. Chilton RLS 1404 monument SW S. 19		
130+87.2	Set $W\frac{1}{4}$ S. 19		
157+04.64	Set SW S. 18		
183+22.08	Set $W\frac{1}{4}$ S. 18		
209+39.52	Set SW S. 7		
235+56.96	Set $W\frac{1}{4}$ S. 7		
		261+74.40	Set SW S. 6
		287+91.84	Set $W\frac{1}{4}$ S. 6
		314+09.28	NW S. 6 T36N, R50E

I, Paul N. Scherbel certify that I have carefully performed and reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

6805

Registration No.

STATE OF ~~WYOMING~~, NEVADA

Office of Clerk and Recorder,

County of EUREKA

This "corner record" was filed for record on the 9th day of November at 11:00 AM, 1984, was noted on the cross-index plat and is assigned page No. 6-25, in book No. 36-49

cc: Chilton
BLM
Cerny
McMahon
Allen S. Gordon

M. J. Rebalante
County Official

Cross Index No.	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.