

21 December 1984

T36N, R50E

97606

Field Date  
25 November 1984

**CERTIFIED LAND CORNER RECORDATION**

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

Record:-- East between Section 34, T36N, R50E and Section 1, T35N, R50E for one-quarter corner of Section 34, T36N, R50E.

40.00 Set a Trap stone 18x20x8 ins. stone mound as per instructions for 1/4 Sec. Cor.

53.66 110 ft. above ravine on E. slope of divide ridge. At proportional distance, set an iron post 3 ft. long, 1 in. in dia., 20 ins. in the ground for the Std. 1/4 Sec. Cor., see below

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set:-- Needs rehabilitation next summer.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.  
(May Sketch or Paste Reproduction on Reverse Side.)

Reference:-- Book NV, page 44.

Record:--  
Continued with brass cap mkd:  
S 34  
1914  
and raise a mound of stone 2 ft. base, 1 1/2 ft. high N. of cor.


Found:-- A 1" black iron pipe with brass cap inscribed as shown



canted and set in mound of stone.

I, Paul N. Scherbel certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve.

*Paul N. Scherbel*  
Signature of Surveyor  
6805  
Registration No.



STATE OF WYOMING, NEVADA  
Office of Clerk and Recorder,  
County of EUREKA

This "corner record" was filed for record on the 2nd day of January, No. 6805-114571-1985, was noted on the cross-index plat and is assigned page No. 7-15, in book No. 36-50.

cc: BLM  
Gordon  
McMahon  
Cerny

*M. J. Reboate*  
County Official

Cross Index No. \_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
 \_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
 \_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
 \_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
 \_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.  
 \_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Mer.

97606