

17 June 1985

T36N, R51W

93502

Field Date
12 June 1985

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

Record:-- North between Section 30, T36N, R51E and Section 22, T36N, R50E for corner common to Sections 30 and 19, T36N, R51E.
80.00 Set a sandstone 19x11x10 ins., 14 ins. in the ground for Cor. to Secs. 19-24-20 & 30 marked with 2 notches on S. and 4 notches on N. edges and raised a mound of stone alongside. Pits impracticable. The necessary correction corresponding to the given slopes has been applied and the corners located according see below

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set:-- Nothing.

**SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)**

Reference:-- Book NV, page 66.

Record:--
Continued to the total distance thus obtained.


Found:-- A 1 1/4" black iron pipe 15" above ground marked // on S, //// on N set in mound of stone. No marked stone found nor stone of record size.

0+00 SW S31, T36N, R51E
50+22.53 SW S30 iron pipe
103+11.30 NW S30 as above

Note:-- Topography calls of field notes do not correspond with conditions on ground.

I, Paul N. Scherbel certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor



6805
Registration No.

STATE OF ~~WYOMING~~ NEVADA
Office of Clerk and Recorder,
County of EUREKA

This "corner record" was filed for record on the 26th day of June at 11:35 A.M., 19 85, was noted on the cross-index plat and is assigned page No. R-1, in book No. 36-51.

cc: BLM
Dominguez
McMahon

M.M. Reboleati
County Official

Cross Index No. _____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.

93502