99503

Field Date 11 June 1985

CERTIFIED LAND CORNER RECORDATION				
Record: 80.00	Set a granite stone 2 to Secs. 25-30-31 on N. edges and ra practicable. The given slopes has b	a 31, T36N, R51W and to Sections 30 and 22x16x12 ins. 16 in & 36 marked with 1 ised a mound of st necessary correctiveen applied and the	d Section 27, 1 31, T36N, R51E s. in the grour notch on S. ar one alongside. ons correspondi e corners locat	36N, R50E ind for Cor. and 5 notches Pits im- ing to the
	DESCRIPTION OF MONUMENTO PERPETUATE THE ORIGI			
Set:	Nothing.			
SKETCH, WITH C	OURSE AND DISTANCE TO A	DIACENT CORNER IF D Reproduction on Reverse		SURVEY.
Reference:	Book NV, page 62.			
Record: Continued	to the total dista	nce thus obtained.		
Found:	A 1.9'x0.9'x0.7' lime in mound of stone marked //// on N,	with a 1½" black i	ron pipe 19" ab	ove ground
Note:	0+0 50+2 Topography calls of f	2.53 SW S30 as ab	ove	conditions
Note: 11	on ground.	retu noces do not	orrespond wren	Concretons
ı Paul N. Sc	herbel	certify that I have gard	etully performed an	reviewed the work
	corner as reported on this rec	Signature of Surveyor (2)	PAUL N.	6805 Registration No.
JIATE OF WAY COMMINSO, NEV		E S		i i
Office of Clerk and Record County of EUREKA	der,	Service Control of the Control of th	No. 6805	J
This "corner record" was fil	led for record on the 20th dis assigned page No. V-1	_, in book No. <u>36-51</u>	11:35 A.M., 1	9 <u>85,</u> was noted
Dominguez		Cross Index No	County Official	R Mer.
McMahon	00500		T T	R Mer. R Mer. R Mer. R Mer.
1	99503		T	R Mer.