

T36N, R50E

104696

3 September 1986

Field Date  
20 August 1986

**CERTIFIED LAND CORNER RECORDATION**

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

Record:-- North between Sections 29 and 30.  
40.00 Set a charred post in mound with pits as per instructions for  
1/4 Sec. Cor.

Found:-- A 2" aluminum pipe with aluminum cap inscribed as shown

see below


DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set:-- Nothing.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.  
(May Sketch or Paste Reproduction on Reverse Side.)

Reference:-- Book NV2, page 4.

Found:--  
Continued



Green steel fence post alongside to W. Sly., 12 ft.± of PNS  
spike set for temp 1/4 corner at 90° from township line and  
1.5 miles N (120 ch).

I, Paul N. Scherbel certify that I have carefully reviewed the work  
done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

PAUL N.  
SCHERBEL

6805

Registration No.

STATE OF ~~WYOMING~~ NEVADA  
Office of Clerk and Recorder,  
County of EUREKA

This "corner record" was filed for record on the 10th day of Sept. at 1:40 p.m., 1986, was noted  
on the cross-index plat and is assigned page No. T-5, in book No. 36-50.

cc: BLM  
Burton

County Official

Cross Index No.	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.