

T36N, R50E

104696

3 September 1986

Field Date
20 August 1986

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

Record:-- North between Sections 29 and 30.
40.00 Set a charred post in mound with pits as per instructions for
1/4 Sec. Cor.

Found:-- A 2" aluminum pipe with aluminum cap inscribed as shown

see below


DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set:-- Nothing.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)

Reference:-- Book NV2, page 4.

Found:--
Continued



Green steel fence post alongside to W. Sly., 12 ft.± of PNS spike set for temp 1/4 corner at 90° from township line and 1.5 miles N (120 ch).


I, Paul N. Scherbel certify that I have carefully reviewed the work done on the diagrammed corner as reported on this recordation form and approved the same.

Signature of Surveyor

6805

Registration No.

STATE OF ~~WYOMING~~ NEVADA
Office of Clerk and Recorder,
County of EUREKA



104696

This "corner record" was filed for record on the 10th day of Sept. at 1:40 p.m., 1986, was noted on the cross-index plat and is assigned page No. T-5, in book No. 36-50.

cc: BLM
Burton

County Official

Cross Index No.	_____ T. _____ R. _____	Mer.
	_____ T. _____ R. _____	Mer.
	_____ T. _____ R. _____	Mer.
	_____ T. _____ R. _____	Mer.
	_____ T. _____ R. _____	Mer.
	_____ T. _____ R. _____	Mer.
	_____ T. _____ R. _____	Mer.