## 117969

## CERTIFICATE OF LOCATION

## LODE CLAIM

On the lith day of April , 1988, situated in the understand District, Eureka County, State of Nevada.  Said claim is located in the NE/4 of Sec. , Twp. North , Range ENW/4 of Sec. 26, Twp. 35 North , Range 51 ENW/4 of Sec. 26, Twp. 35 North	
P.O. Box 548, 135 East Second Avenue Battle Mountain, Nevada 89820  In the	
P.O. Box 548, 135 East Second Avenue Battle Mountain, Nevada 89820  In the	
Battle Mountain, Nevada 89820  a the	
aid claim is located in the NE/4 of Sec. Twp. North Range SE/4 of Sec. Z6, Twp. North Northeast corner of Sec. Z6, Twp. North Range SE/4 of Sec. Z6, Twp. North Range	
strict, Eureka county, strict, europe county, strict, content, strict, strict, europe county, europe count	
strict, Eurexa country, the strict, Eurexa country, and claim is located in the NE/4 of Sec	lining
id claim is located in the NE/4 of Sec, Twp	
SE/4 of Sec, Twp. North , Range	• 2 *
SE/4 of Sec	
SE/4 of Sec	ast
SW/4 of Sec. 26, Twp. 35 North, Range 51 E  tie this claim to the Public Survey, begin at the Southeast corner of Sec. 33	ast .
SW/4 of Sec. 26, Twp. 35 North, Range 51 E  tie this claim to the Public Survey, begin at the Southeast corner of Sec. 33	ast .
tie this claim to the Public Survey, begin at the Southeast corner of Sec 33 , Township 35 North , Range 51 East , Mount Diablo Meridian, 8000 feet North and 7200 feet East to the Northeast corners claim.  e (or I) claim 1500 linear feet along the course of the ledge, lode or vertending 1490 feet from the location monument in a Northerly direction feet in a Southerly direction, together with 300 feet on east fithe center of the ledge for the entire length of the claim.  The exterior boundaries of this claim are clearly marked by substantial PVC concuments firmly set in the ground and bearing applicable monument designation. Secription of such claim is: Beginning at the Northeast corner: thence, South , 750 feet to the Southeast corner; thence, West , 6000 feet to the Southeast corner, thence, North , 750 feet to the Southwest corner, thence, North , 750 feet to the Northwest corner, thence, North , 750 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence , East , 600 feet to the Northwest corner, thence , East , 600 feet to the Northwest corner, thence , East , 600 feet to the Northwest corner, thence , East , 600 feet to the Northwest corner, thence , East , 600 feet to the Northwest corner, thence , East , 600 feet to the Northwest corner, thence , East , 600 feet to the Northwest corner, thence , East , 600 feet to the Northwest corner, thence , East , 600 feet to the Northwest corner, the provided by the Late NPS 517,040.	ast .
8000   feet   North   and   7200   feet   East   to the Northernois claim.  e (or I) claim   1500   linear feet along the course of the ledge, lode or vertending   1490   feet from the location monument in a   Northerly   direction   Northerly	
8000   feet   North   and   7200   feet   East   to the Northest    e (or I) claim   1500   linear feet along the course of the ledge, lode or vertending   1490   feet from the location monument in a   Northerly   direction    feet in a   Southerly   direction, together with   300   feet on east    f the center of the ledge for the entire length of the claim.  The exterior boundaries of this claim are clearly marked by substantial   PVC    Nonuments firmly set in the ground and bearing applicable monument designation.  Rescription of such claim is:   Beginning at the Northeast corner:    thence,   South   750   feet to the   East   side center,    thence,   South   750   feet to the   Southwest   corner,    thence,   West   600   feet to the   West   side center,    thence,   North   750   feet to the   Northwest   corner,    thence,   North   750   feet to the   Northwest   corner,    thence,   East   600   feet to the   Northwest   corner,    thence,   East   600   feet to the   Northwest   corner,    thence,   East   600   feet to the   Northwest   corner,    the monumentation and marking of the corners was completed by the   13th    April   1988.	
8000   feet   North   and   7200   feet   East   to the Northernois claim.  e (or I) claim   1500   linear feet along the course of the ledge, lode or vertending   1490   feet from the location monument in a   Northerly   direction   Northerly	tion
8000   feet   North   and   7200   feet   East   to the Northernois claim.  e (or I) claim   1500   linear feet along the course of the ledge, lode or vertending   1490   feet from the location monument in a   Northerly   direction   Northerly	thence
## North   1500   linear feet along the course of the ledge, lode or vertending   1490   feet from the location monument in a   Northerly   direction   10   feet in a   Southerly   direction, together with   300   feet on early   feet in a   Southerly   direction, together with   300   feet on early   feet in a   Southerly   direction, together with   300   feet on early   feet in a   Southerly   direction, together with   300   feet on early   feet in a   Southerly   feet on early   feet   fee	er or
thence, South , 750 feet to the thence, North , 750 feet to the Northwest corner, thence, North , 750 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence , East , 600 feet to the Northwest corner, thence , East , 600 feet to the Northwest corner, the feet of the Northwest corner.	
feet in a Southerly direction, together with 300 reet on early the center of the ledge for the entire length of the claim.  The exterior boundaries of this claim are clearly marked by substantial PVC comments firmly set in the ground and bearing applicable monument designation.  The exterior boundaries of this claim are clearly marked by substantial PVC comments firmly set in the ground and bearing applicable monument designation.  The market set in the ground and bearing applicable monument designation.  The market set in the ground and bearing applicable monument designation.  The market set in the ground and bearing applicable monument designation.  The monumentation and marking of the corners was completed by the 13th April 1988.	
feet in a Southerly direction, together with 300 reet on early feet in a Southerly direction, together with 300 reet on early feet in a Southerly direction, together with 300 reet on early feet in the ledge for the entire length of the claim.  The exterior boundaries of this claim are clearly marked by substantial PVC consuments firmly set in the ground and bearing applicable monument designation.  The manufacture in the ground and bearing applicable monument designation.  The manufacture in the ground and bearing applicable monument designation.  The monumentation and marking of the corners was completed by the 100 reet on the 100 reet of the 10	and
f the center of the ledge for the entire length of the claim.  the exterior boundaries of this claim are clearly marked by substantialPVC_  nonuments firmly set in the ground and bearing applicable monument designation.  escription of such claim is: Beginning at the Northeast corner:  thence, South , 750 feet to the	ch side
thence, South , 750 feet to the thence, South , 750 feet to the thence, South , 750 feet to the thence, West , 600 feet to the thence, North , 750 feet to the thence, North , 750 feet to the thence, West , 600 feet to the thence, North , 750 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, The monumentation and marking of the corners was completed by the 13th April , 1988.	
thence, South , 750 feet to the Southeast corner, thence, West , 600 feet to the thence, North , 750 feet to the thence, Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, North , 600 feet to the the thence, Northwest corner, thence, Northwest corner, thence, Northwest corner, thence, Northwest corner, Northwest corner, thence, Northwest corner, Northwe	
thence, South , 750 feet to the Southeast corner, thence, North , 750 feet to the Southeast corner, thence, North , 750 feet to the Southeast corner, thence, North , 750 feet to the Hence, North , 750 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northeast corner, thence, East , 600 feet to the Northeast corner, thence, East , 600 feet to the Northeast corner, thence, East , 600 feet to the Northeast corner, thence, East , 600 feet to the Northeast corner, thence, East , 600 feet to the Northeast corner, corner, thence, East , 600 feet to the Northeast corner, corner, thence, East , 600 feet to the Northeast corner, co	Pipe
thence, South , 750 feet to the Southeast corner, thence, North , 750 feet to the thence, Nort	The
thence, South, 750 feet to the thence, South, 750 feet to the thence, South, 750 feet to the thence, West, 600 feet to the thence, North, 750 feet to the thence, East, 600 feet to the Northwest corner, the East corner, the East corner, the East corner, the East corner, East corner, the East corner, East c	
thence, South , 750 feet to the Southeast corner, thence, West , 600 feet to the Southwest corner, thence, North , 750 feet to the West side center, thence, North , 750 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, and marking of the corners was completed by the 13th April , 1988.	
thence, South , 750 feet to the Southeast corner, thence, West , 600 feet to the thence, North , 750 feet to the thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, The	
thence, South , 750 feet to the Southwest corner, thence, North , 750 feet to the Hence, North , 750 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, Tast , 600 feet to the Northwest corner, thence, Tast , 600 feet to the Northwest corner, the point and place of beginning.  The monumentation and marking of the corners was completed by the 13th April , 1988.	
thence, North, 750 feet to the West side center, North thence, North, 600 feet to the Northwest corner, thence, East , 600 feet to the Northwest corner, thence, or the monumentation and marking of the corners was completed by the 13th April , 1988.	·* 2
thence, North, 750 feet to the Northwest corner, thence, East, 600 feet to the Northeast corner, thence, East, 600 feet to the Northeast corner, the monumentation and marking of the corners was completed by the 13th April , 1988.	
thence, North , 70 feet to the Northeast corner, thence, East , 600 feet to the Northeast corner, the point and place of beginning.  The monumentation and marking of the corners was completed by the 13th April , 1988.	
thence, East, 5000  the point and place of beginning.  the monumentation and marking of the corners was completed by the 13th April , 1988.	÷.
the point and place of beginning.  The monumentation and marking of the corners was completed by the 13th April , 1988.	
The monumentation and marking of the corners was completed by the 13th April , 1988.	
The monumentation and marking of the corners was completed by the 13th April , 1988.	
April , 1980.	day of
April , 1980.	
County Recorded	
consisted of making a claim map as provided in NKS 317.040.	Two
	and
The location work consisted of making a claim map as provided in has 32 context.  County Recorder copies of this claim map have been filed with the Eureka County Recorder.	
copies of this claim map have been filed with the county Recorder. the lode claim filing fee has been paid to the County Recorder.	4.
TOCATORS Horseshoe Gold Mining	, Inc.
LOCATORS Horseshoe Gold Hilling	1
RECORDER AT THE REQUEST OF  Douglas F. Sterck, As	<u></u>
RECORDER AT THE RELUCE STREET BOURGES F. Sterck, Ag	ent
800K 1.7.6_PAGE	
188 APR 25 P4:44	
PERFORM STORES	
OFFICIAL PECORDS  FURENA COUNTY REVADA MIN. REDALEST. RESORDER 17969	
HN REDALLATI RECORDE 17969	
FILE N. C. Z.S.	