

23 September 1988

T36N, R49E

Field Date
7 September 1988

124963

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

Record:-- 1872 - North, between sections 15 and 16.
80.00 Set a Red Granite Stone 24x16x14 as per instructions for
Corner to secs. 9-10-15 and 16.

Found:-- A red granite stone 0.8 ft.x0.8 ft.x0.8 ft. marked /// on E,
// on N with a 5/8" steel reinforcing rod bears SWly., 0.9
ft. measured from hightop point of marked stone and a red,
see below

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set:-- An electrical power pole bears NWly., 108.33 ft. and an E/W
5 B/W fence bears Sly., 210.5 feet on section line.
Built mound of stone to west as original stone mound stones are
supporting aerial photography control paneling.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)

Reference:-- Book NV2, page 16.

Found:--
Continued steel fence post bears SWly., 1.25 feet.

I, Paul N. Scherbel certify that I have carefully performed or reviewed the work
done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor


6805

Registration No.

STATE OF ~~WYOMING~~ NEVADA

Office of Clerk and Recorder,

County of EUREKA



This "corner record" was filed for record on the 28th day of Nov, 1988, was noted
on the cross-index plat and is assigned page No. 1-13, in book No. 36-49

M. N. Reboletti
County Official

cc: BLM
Hull
Terry

Cross Index No.	_____ T. _____ R. _____ Mer.
_____	_____ T. _____ R. _____ Mer.
_____	_____ T. _____ R. _____ Mer.
_____	_____ T. _____ R. _____ Mer.
_____	_____ T. _____ R. _____ Mer.
_____	_____ T. _____ R. _____ Mer.
_____	_____ T. _____ R. _____ Mer.

124963