

23 September 1988

T36N, R49E

Field Date
7 September 1988

124965
CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

Record:-- 1872 - North, between Sections 15 and 16.
40.00 Set a red Granite Stone 16x15x14 as per instructions for
1/4 Sec. Cor.

Found:-- A red granite stone 18"x12"x12" marked with 1/4 on W. with a
red steel fence post lying unset to W. Monument and steel
fence post had been flattened by electrical power line see below

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set:-- Reset original marked stone in original position alongside
to E, piece of steel fence post remaining in ground.
Set steel fence post alongside to west. Built mound of
stone in tire casing to W. Buried fence post guide
plate alongside to E. of monument. Monument is SEly.,
63.7 feet from electrical power pole.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)


Reference:-- Book NV2, page 16.

Found:--
Continued construction. Upon digging found a severed piece of
steel post still in place in ground.

I, Paul N. Scherbel certify that I have carefully performed or reviewed the work
done on the diagrammed corner as reported on this recordation form and approve the same.

Paul N. Scherbel Signature of Surveyor 6805 Registration No.

STATE OF ~~WYOMING~~ NEVADA
Office of Clerk and Recorder,
County of EUREKA



This "corner record" was filed for record on the 28th day of Nov, 1988, was noted
on the cross-index plat and is assigned page No. L-13, in book No. 36-49.

cc: BLM
Hull
Terry

M. P. Roberts
County Official

Cross Index No. _____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.

124965