124967

Field Date 19 September 1988

. R. _

CERTIFIED LAND CORNER RECORDATION DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known) Record: -- 1872 - North, between Sections 23 and 24. 80.00 Set a charred post in mound with pits as per instructions for Corner to Secs. 13-14-23 and 24. No evidence of the original survey after exhaustive search. Found: --DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: Set:--A 2" galvanized steel pipe 31" long (BLM type) with brass cap inscribed as shown see below SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.) Book NV2, pages 33, 36. Reference: --Set:--Continued RLS6805 T36N R49E S23 | S24 JUAG at the point determined by double proportionate measurement. Built a mound of stone in tire casing to W. 80.10 15956.99 240.10 5323.43' from NE S.24 80 320 21028.00 5257.00'S Paul N. Scherbel certify that I have care done on the diagrammed corner as reported on this recordation form and ag 6805 Signature of Sur Registration No. PAUL N. SCHERBEL STATE OF WAR MANY, NEVADA ice of Clerk and Recorder, -- Junty of ___EUREKA No. 6805 . 1988, was noted This "corner record" was filed for record on the_ day of __ on the cross-index plat and is assigned page No. N-21, in book No. 36-49 M.M. Reboleati BLM cc: Hull County Official Terry Cross Index No. 124967 _ R. _____