

23 September 1988

T36N, R49E

124967

Field Date
19 September 1988

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

Record:-- 1872 - North, between Sections 23 and 24.
80.00 Set a charred post in mound with pits as per instructions for
Corner to Secs. 13-14-23 and 24.

Found:-- No evidence of the original survey after exhaustive search.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:


Set:-- A 2" galvanized steel pipe 31" long (BLM type) with brass cap
inscribed as shown

see below

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)

Reference:-- Book NV2, pages 33, 36.

Set:--
Continued




at the point determined by double proportionate measurement.
Built a mound of stone in tire casing to W.

$$\begin{array}{r} 80.10 \\ \hline 240.10 \end{array} = \frac{X}{15956.99} = 5323.43' \text{ from NE S.24}$$

$$\begin{array}{r} 80 \\ \hline 320 \end{array} = \frac{X}{21028.00} = 5257.00'S \text{ of NW S.13}$$

I, Paul N. Scherbel certify that I have carefully reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor



6805
Registration No.

STATE OF ~~NEVADA~~ NEVADA

Office of Clerk and Recorder,

County of EURKA

This "corner record" was filed for record on the 28 day of Nov, 1988, was noted on the cross-index plat and is assigned page No. N-21, in book No. 36-49.

cc: BLM
Hu11
Terry

M. N. Rebovanti
County Official

Cross Index No.	_____ T.	_____ R.	_____ Mer.
	_____ T.	_____ R.	_____ Mer.
	_____ T.	_____ R.	_____ Mer.
	_____ T.	_____ R.	_____ Mer.
	_____ T.	_____ R.	_____ Mer.
	_____ T.	_____ R.	_____ Mer.

124967