124970

Field Date

20 September 1988 15 October 1988

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

Record: -- 1872 - North, between Sections 23 and 24.

40.00 Set a charred post in mound with pits as per instructions for 1 Sec. Cor.

Found: --

Nothing after intensive search.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set:--

A 2" galvanized steel pipe 31" long (BLM type) with brass cap inscribed as shown

see below

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)

Reference:--

Book NV2, pages 37, 38, 39, 40.

Set:--Continued



at reestablished position. Built a mound of stone to E in tire casing. Monument is in alluvium material of gully - wash area.

> 0+00 NW S.24 26+28.39 Set 🕯 monument as above 52+56.78 SW S.24

	<u>/</u>		
. Paul N. Scherbel		e carefull er er lorra	or reviewed the work
done on the diagrammed corner as reported on	this recordation form and	approxie the Wall From	TO STATE OF THE ST
	Land of	B. S. Saring	6805
^	Signature of Surveyo		Registration No.
STATE OF THE STATES, NEVADA	·	PAUL N.	<u> </u>
1 3		SCHERBEL SCHERBEL	§ ₹ Ø
ice of Clerk and Recorder,		Na g	SA
County of EUREKA		Mary Booon	40 A
This "corner record" was filed for record on the	28 day of nov-	No. 6805	984_, was noted
on the cross-index plat and is assigned page No	o. P-21, in book No. 36-	49	
Of the cross mack but our is accident below	•	m. 97. Rel	rleadi
cc: BLM			
Hull		County Official	
Terry	Cross Index No.	T	
Summit		<u>T</u>	— ;;;
1249	124970		R Mer.
		<u> </u> ,	R Mer. R Mer.
		<u> </u>	R Mer.
	•		_ K