Field Date 4 September 1988

CERTIFIED LAND CORNER RECORDATION
DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)
Record: 1872 - North bet. Sections 28 and 29. 80.00 Set a charred post in mound with pits as per instructions for Corner to Secs. 20-21-28-29. 1914 - N. bet. Secs. 28 and 29, retracing. 79.90 I find the cor. of secs. 20, 21, 28 29; falling 44 lks. E. of my line. It is a stake 2 ins. diam. by 15 ins. long, laying on the ground on a mound of earth and mkd. with 4 and 2 see be
DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:
Set: Enlarged mound of stone in tire casing to W.
SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.) Reference: Book NV2, page 9.
Record:
Continued notches on the edges. 79.90 The cor. of secs. 20, 21, 28 and 29. I destroy all traces of this cor. and its accessories and
reetablish it at the same point as follows:
Set a basalt stone 15x12x7 ins., 10 ins. in the ground for cor. of secs. 20, 21, 28 and 29; mkd. with 4 notches on the E and
2 notches on the S. edge, and raise a mound of stone 2 ft. base l½ ft. high W. of cor.
Found: A hard, red granite stone 1.0'x0.8'x0.8' above ground marked with 2 large notches on S and 4 large notches on E. Large mound of large stones to W. A red steel fence post bears NEly., 1.6 ft.
I, Paul N. Scherbelcertify that have carefully processed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the part to be a second or the work done on the diagrammed corner as reported on this recordation form and approve the part to be a second or the work done on the diagrammed corner as reported on this recordation form and approve the part to be a second or the work done on the diagrammed corner as reported on this recordation form and approve the part to be a second or the work done on the diagrammed corner as reported on this recordation form and approve the part to be a second or the diagrammed corner as reported on the work done on the diagrammed corner as reported on this recordation form and approve the part to be a second or the work done on the diagrammed corner as reported on this recordation form and approve the part to be a second or the diagrammed corner as reported on this recordation form and approve the part to be a second or the diagrammed corner as reported or the part to be a second or the diagrammed corner as reported or the part to be a second or the diagrammed corner as reported or the part to be a second or the diagrammed corner as the part to be a second or the diagrammed corner as the part to be a second or the diagrammed corner as the part to be a second or the diagrammed corner as the dia
Signature of Surveyor Signature of Surveyor Registration No.
TE OF WATERIES, NEVADA  se of Clerk and Recorder,
ce of Clerk and Recorder,
County of EUREKA
This "corner record" was filed for record on the 28th day of No. 36-49 was noted on the cross-index plat and is assigned page No. R-9, in book No. 36-49
CC: BLM
Hull Terry Cross Index No
T R Mer.
T D Mor
124972 T R Mer