

21 September 1988

T36N, R49E

124974

Field Date  
5 September 1988

**CERTIFIED LAND CORNER RECORDATION**

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

Record:-- 1872 - North bet. Secs. 27 and 28.  
 80.00 Set a charred post in mound with pits as per instructions for Corner to Secs. 21-22-27 and 28.  
 1914 - E. bet. Secs. 21 and 28; retracing.  
 80.26 I find the cor. of Secs. 21, 22, 27 and 28; falling 23 lks. N. of my line. It is a stake 2 ins. diam. by 14 ins. above ground; set in the ground in a mound of earth and  
 see below

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set:-- A 2" galvanized steel pipe 31" long (BLM type) with brass cap inscribed as shown  
 see below

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)

Reference:-- Book NV2, pages 10-11.


Record:-- mkd. with 2 notches on the E. and 2 notches on the S. edge.  
 Continued 80.26 The cor. of Secs. 21, 22, 27 and 28. I destroy all traces of this cor. and its accessories and re-establish it at the same point as follows:  
 Set a basalt stone 15x8x8 ins. 10 ins. in the ground for cor. of secs. 21, 22, 27 and 28; mkd. with 2 notches on the E. and 2 notches on the S. edge; dig pits 18x18x12 ins. in each sec. 5 1/2 ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high E. of cor.

Found:-- As there appeared to be no evidence of the stone monument, the location for reestablishment was run in from the S 1/2 of Section 21 and E 1/2 Section 21 as for a two line double proportionate reestablishment. This indicated that the monuments should be in the position of the corner RR tie fence post. In digging the hole to set a monument the original stone was recovered which is a hard, red granite stone broken into two pieces 15"x11"x8" marked with 2 notches on S. and E. alongside to E. of RR tie fence post.

Set:-- Continued see reverse side

I, Paul N. Scherbel certify that I have carefully reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor: Paul N. Scherbel Registration No. 6805



STATE OF ~~SPRING~~ NEVADA  
 of Clerk and Recorder,  
 County of EUREKA

This "corner record" was filed for record on the 28<sup>th</sup> day of Nov, 1988, was noted on the cross-index plat and is assigned page No. R-13, in book No. 36-49.

cc: BLM  
 Hull  
 Terry

M. J. Rebeck  
 County Official

Cross Index No.	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.

124974