

23 September 1988

T36N, R49E

Field Date
10 September 1988

124978

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

Record:-- 1872 - North, between Sections 28 and 29.
40.00 Set a charred post in mound with pits as per instructions for 1/4 Sec. Cor.
1914 - N. bet. secs. 28 and 29, retracing.
40.00 I search diligently but find no 1/4 sec. cor.
N00°-19'E, bet. secs. 28 and 29.
39.95 (Proportional Distance) Set an iron post 3 ft. long, 1 in. *see below*

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:


Set:-- Built mound of stone in tire casing to west.
Monument is in open area recently burned over with a cover of cheat grass and crested wheat grass.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)

Reference:-- Book NV2, page 22.


Record:-- diam. 24 ins. in the ground for 1/4 sec. cor. with brass cap
Continued mkd.
S29 1/4 | S28
1914
dig pits 18x18x12 ins. N and S of post 3 ft. dist. and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high W. of cor.

Found:-- A 1" black iron pipe with brass cap inscribed as shown



I, Paul N. Scherbel certify that I have carefully performed and reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor



6805

Registration No.

STATE OF ~~NEVADA~~ NEVADA

Office of Clerk and Recorder,

County of EUREKA

This "corner record" was filed for record on the 28th day of Nov, 1988, was noted on the cross-index plat and is assigned page No. I-9, in book No. 36-49

M. J. Reblentz

cc: Hull
Terry
BLM

County Official

Cross Index No. _____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.

124978