

T36N, R49E

23 September 1988

Field Date
5 September 1988

124981

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

Record:-- 1872 - East on south boundary Section 32.
40.00 Set a charred post in mound with pits as per instructions
for $\frac{1}{4}$ Sec. Cor.
1914 - E. on 7th Standard Parallel North, south of sec. 32.
40.00 I search diligently but find no standard $\frac{1}{4}$ sec. cor.
N89°-56'E, on the 7th Standard Parallel North; S. of sec. 32.
40.09 (Proportional distance) Set an iron post 3 ft. long, 1 in. see below

**DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

Set:-- Straightened pipe and turned so that it reads correctly.

**SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)**

Reference:-- Book NV2, page 12.

Record:-- diam. 24 ins. in the ground for standard $\frac{1}{4}$ sec. cor. with
Continued brass cap mkd.

S32 $\frac{1}{4}$
SC


1914.

Found:-- A canted 1" black iron pipe with brass cap turned 180°
inscribed as shown.



I, Paul N. Scherbel certify that I have carefully performed or reviewed the work
done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor



Registration No.

STATE OF ~~WYOMING~~ NEVADA

Office of Clerk and Recorder,

County of EUREKA

This "corner record" was filed for record on the 28th day of Nov, 1988, was noted
on the cross-index plat and is assigned page No. 2-7, in book No. 36-49.

cc: BLM
Hull
Terry

County Official

Cross Index No.	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.
	T.	R.	Mer.

124981