

23 September 1988

T36N, R49E

Field Date
5 September 1988

124981

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)

Record:-- 1872 - East on south boundary Section 32.
 40.00 Set a charred post in mound with pits as per instructions for 1/4 Sec. Cor.
 1914 - E. on 7th Standard Parallel North, south of sec. 32.
 40.00 I search diligently but find no standard 1/4 sec. cor. N89°-56'E, on the 7th Standard Parallel North; S. of sec. 32.
 40.09 (Proportional distance) Set an iron post 3 ft. long, 1 in. *see below*

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set:-- Straightened pipe and turned so that it reads correctly.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY. (May Sketch or Paste Reproduction on Reverse Side.)

Reference:-- Book NV2, page 12.

Record:-- diam. 24 ins. in the ground for standard 1/4 sec. cor. with
Continued brass cap mkd.


S32 1/4
SC
1914.

Found:-- A canted 1" black iron pipe with brass cap turned 180° inscribed as shown.



I, Paul N. Scherbel certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor



Registration No.

STATE OF ~~WYOMING~~ NEVADA

Office of Clerk and Recorder,

County of EUREKA

This "corner record" was filed for record on the 28th day of Nov, 1988, was noted on the cross-index plat and is assigned page No. 2-7, in book No. 36-49.

cc: BLM
Hull
Terry

County Official

Cross Index No. _____ T. _____ R. _____ Mer.
 _____ T. _____ R. _____ Mer.
 _____ T. _____ R. _____ Mer.
 _____ T. _____ R. _____ Mer.
 _____ T. _____ R. _____ Mer.
 _____ T. _____ R. _____ Mer.

124981