- Revised -

124982

CERTIFIED LAND CORNER RECORDATION	
DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (If known)	
Record: See Certificates dated 25 August and 25 October 1984. 1986 - NOO°-04'E, beginning new measurement. 38.25 Point selected for the witness cor. of secs. 25, 30, 31 and 36. Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 i in the ground to solid rock and in a mound of stone, base to top, with aluminum (cap) mkd.	ns.
DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:	
Set: Monument is Sly., 4 ft. of edge of near vertical mining	pit.
Chilton and PNS monuments are no longer at the corner location.	
SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SUI	RVEY.
(May Sketch or Paste Reproduction on Reverse Side.) Reference: Book NV2, page 13.	
Record: Continued WC T36N R49E R50E S25 S30 S36 S31 1986	
Set a steel fence post, 5½ ft. long, alongside the alum post. 39.65 True point for the cor. of secs. 25, 30, 31, and 36, at proportionate distance; falls on S. edge of mining p where it is impracticable to establish a permanent monument; there is no remaining evidence of the orig corner. Found: As described without steel fence post. Also found were PNS 3/8"x12" steel spikes at position W ft., 400 ft., and 500 ft. @90° from range line which	it, inal
be used to relocate and reestablish PNS monument.	
done on the diagrammed corner as reported on this recordation form and appropriate the same of the sam	ewed the work
- Jul & Side with 2	6805
Signature of Surveyor PAIL N	Registration No.
STATE OF TATOMING, NEVADA ce of Clerk and Recorder, July of EUREKA This "corner record" was filed for record on the day of the cross-index plat and is assigned page No. V-25, in book No. 36-49	5, was noted
me cross-mack plat and is assigned page to the page of	<i>k.</i> ,
cc: BLM Hull County Official	
Terry Cross Index No T R	
T R T R	
T R	Mer.
124982TR	
T R	