

24 October 1988

T36N, R49E

124983

Field Date
15 October 1988

- Revised -

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (if known)

Record:-- N00°-04'E between Section 36, T36N, R49E and Section 31, T36N, R50E for one-quarter corner.
39.67 The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set showing 6 ins. above ground. This monument is accepted as a careful and faithful perpetuation of the position of the original corner with brass cap mkd.

see below

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set:-- Changed S31 to S36
Changed S36 to S31
Added BLM 1986


SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNER IF DETERMINED IN THIS SURVEY.
(May Sketch or Paste Reproduction on Reverse Side.)

Reference:-- Book NV2, page 39.

Record:-- PAUL N SCHERBEL
Continued T36N
R49E R50E
S 36 | S 31
RLS 6805
1984

Add the marks BLM 1986 to the brass cap.

Found:-- A 2" galvanized steel pipe with brass cap inscribed as shown




set in tire casing filled with earth and mound of stones atop.

I, Paul N. Scherbel certify that I have carefully performed or supervised the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

6805

Registration No.



STATE OF ~~WYOMING~~, NEVADA

Office of Clerk and Recorder,

City of EUREKA

This "corner record" was filed for record on the 28th day of Nov, 1988, was noted on the cross-index plat and is assigned page No. X-25, in book No. 36-49.

cc: BLM
Hull
Terry

Cross Index No. _____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.
_____ T. _____ R. _____ Mer.

124983