Field Date 5 September 1988

CERTIFIED LAND CORNER I	RECORDATION
Standard Corner to Sect 1914 - E. on the 7th Standard Para 80.18 I find the standard cor. of of my line. It is a sta ground; set in the groun 4 notches on the E. and DESCRIPTION OF MONUMENT AND A	ion 32. with pits as per instructions for ions 32 & 33. llel North, south of sec. 32. secs. 32 and 33, falling 9 lks. N. ke 2½ ins. diam. by 16 ins. above d in a mound of earth and mkd. with 2 notches on the W. edge see belocessories established
TO PERPETUATE THE ORIGINAL LOCA	ATION OF THIS CORNER:
Set: Straightened canted pipe an	d enlarged mound of stones.
SKETCH, WITH COURSE AND DISTANCE TO ADJACENT	
(May Sketch or Paste Reproduction Reference: Book NV2, page 12.	n on Reverse Side.)
	which but the stake is so hadly
Continued weathered that they are N89°-56'E, on the 7th Stand	lard Parallel North; S. of sec. 32.
reestablish it at the sa Set an iron post 3 ft. long	me point as follows: , 3 ins. diam. 24 ins. in the ground s. 32 and 33; with brass cap mkd.
T36N	
R46E S32 S33 S C T914 and raise a mound of sto l½ ft. high N. of cor. Found: A 3" galvanized steel pipe brass cap inscribed as s Large mound of large sto	canted with hown. ne to N.
	hat I have carefully performed of reviewed the work
done on the diagrammed corner as reported on this recordation fo	of Surveyor and SCHERHEL Registration No.
TE OF WATERARY, NEVADA	Visity Sara
ce of Clerk and Recorder,	Maria Constant of the Constant
County of EUREKA	No. 6805
This "corner record" was filed for record on the day of on the cross-index plat and is assigned page No. Z-9, in book	No. 36-49 , 19.88 , was noted
cc: BLM	M. D. Relalast
Hull Terry	County Official
Cross Ir	ndex No T R Mer T R Mer.
	TRMer.
	T R Mer.
124984	T R Mer Mer Mer.
-	T R Mer.