

## MONUMENT DESCRIPTIONS

### 0001

SUMMIT ENG **CONTROL PT** 

SET 5/8" REBAR WITH 1.3" DIAMETER PLASTIC CAP WITH MARKINGS AS SHOWN TO THE LEFT. CONTROL POINT IS LOCATED APPROXIMATELY 150' SOUTHEASTERLY OF THE INTERSECTION OF THE MAIN ROAD TO ROBERTS CREEK RANCH AND THE OLD PONY EXPRESS TRAIL. POINT IS 1.5' EAST OF A WOODEN SIGN THAT READS "ROBERTS CREEK MOUNTAIN HABITAT MANAGEMENT AREA".

### SURVEYING T22N R50E 14 | 13

23 24


MS 5041

MS 5042


MS5043

SECTION CORNER FOR SECTIONS 13, 14, 23, & 24, T22N, R50E, MDM. FOUND 3.25" DIAMETER ALUMINUM CAP ON 2.5" DIAMETER ALUMINUM POST LOCATED 6" WEST OF BURIED STONE. UNEARTHED 17"X14"X6" LIMESTONE WITH 3 NOTCHES ON ONE CORNER AND 1 NOTCH ON ANOTHER. PLACED STONE BACK IN FOUND POSITION AND ACCEPTED ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS 6" ABOVE THE GROUND IN AN AREA OF PINIONS AND JUNIPERS. AN OLD T-POST WAS FOUND APPROXIMATELY 1' NORTH OF

### 4010




QUARTER CORNER COMMON TO SECTION 13 AND SECTION 24, T22N, R50E, MDM. NO ORIGINAL EVIDENCE FOUND. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS 1" ABOVE THE GROUND IN AN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER.




SECTION CORNER FOR SECTIONS 13 & 24, T22N, R50E, MDM., AND SECTIONS 18 & 19, T22N, R51E, MDM. FOUND 11"X9"X6" STONE FIRMLY SET IN THE GROUND IN THE CENTER OF A 3' DIAMETER MOUND OF STONE. STONE HAS 3 GROOVES (2 HORIZONTAL AND 1 DIAGONAL) ON THE NORTH FACE. NO OTHER GROOVES APPARENT. ACCEPTED AS THE ORIGINAL MONUMENT REMOVED STONE, AND IN THE STONE'S FOOTPRINT, SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH THE GROUND IN AN AREA WITH BRUSH AND JUNIPER. PLACED ORIGINAL STONE .5' SOUTH OF OF CORNER AND SET T-POST 1' NORTH OF CORNER. REFER TO REFERENCE #4 & #6.

### 4040



QUARTER CORNER COMMON WITH SECTIONS 19 & 20, T22N, R51E, MDM. FOUND 12"X8"X4" LIMESTONE, LAYING OVER, WITH "1/4" SCRIBED ON FACE, IN THE CENTER OF A 3' DIAMETER IMBEDDED MOUND OF STONE. ACCEPTED AS THE ORIGINAL MONUMENT. REMOVED STONE, AND IN THE STONE'S FOOTPRINT, SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS 1" ABOVE THE GROUND IN AN AREA WITH BRUSH, PINIONS, AND JUNIPERS. PLACED ORIGINAL STONE .5' SOUTH OF OF CORNER AND SET T-POST 1' NORTH OF CORNER.

### 4050



QUARTER CORNER BETWEEN SECTION 24, T22N, R50E, MDM., AND SECTION 19, T22N, R51E, MDM. NO ORIGINAL EVIDENCE FOUND. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION ALONG THE RANGE LINE (FROM #4020 TO #4170). SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN PREVIOUSLY CULTIVATED AREA. SET T-POST 1' NORTH OF CORNER.

#### 4060



QUARTER CORNER COMMON TO SECTION 23 AND SECTION 24, T22N, R50E, MDM. NOTHING FOUND. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH THE GROUND IN AN AREA OF SAGE AND JUNIPERS. CORNER IS LOCATED APPROXIMATELY 2' EAST OF A SMALL DRAINAGE. SET T-POST 1 NORTH OF CORNER.


INIT ENG T22N R50E S23 | S24 S26 S25 7 2012 7 S 1522h

SECTION CORNER FOR SECTIONS 23, 24, 25, & 26, T22N, R50E, MDM. FOUND 4"X6"X2' WEATHERED WOOD POST AND OTHER POST REMNANTS. NO VISIBLE SCRIBING ON POST. NO SUBSURFACE EVIDENCE OF WOOD POST WAS FOUND. NO EVIDENCE OF ORIGINAL 15"X8"X5" LIMESTONE WAS FOUND. ACCEPTED AS THE BEST EVIDENCE OF THE ORIGINAL CORNER. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH THE GROUND IN AN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER AND WIRED WOOD POST REMNANTS TO THE T-POST.



QUARTER CORNER COMMON TO SECTION 24 AND SECTION 25, T22N, R50E, MDM. FOUND NUMEROUS SMALL (3" LONG AND LESS) WOOD REMNANTS LAYING IN A 25' DIAMETER AREA. NO SUBSURFACE EVIDENCE OF WOOD POST WAS FOUND. COULD NOT ESTABLISH LOCATION OF ORIGINAL MONUMENT. WOOD REMNANTS NOT HELD FOR THE RESTORATION OF THIS CORNER. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH THE GROUND IN AN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER.

#### 4090




SECTION CORNER FOR SECTIONS 24 & 25, T22N, R50E, MDM., AND SECTIONS 19 & 30, T22N, R51E, MDM. NO ORIGINAL EVIDENCE FOUND. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION ALONG THE RANGE LINE (FROM #4020 TO #4170). SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH THE GROUND. CORNER IS LOCATED IN CORRAL AREA OF ROBERTS CREEK RANCH IN THE APPROXIMATE CENTERLINE OF A DIRT ROAD. SET T-POST 1' NORTH OF CORNER.



QUARTER CORNER COMMON WITH SECTIONS 19 & 30. T22N, R51E, MDM. FOUND 12"X10"X6" LIMESTONE, LAYING OVER, WITH "1/4" SCRIBED ON EXPOSED SIDE FACING NORTH. ACCEPTED AS THE ORIGINAL MONUMENT. REMOVED STONE, AND IN THE STONE'S FOOTPRINT, SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH THE GROUND IN AN AREA WITH SAGEBRUSH. PLACED ORIGINAL STONE .5' SOUTH OF OF CORNER AND SET T-POST 1' NORTH OF CORNER. FROM THIS CORNER A 24" DIAMETER JUNIPER BEARING TREE WITH OPEN BLAZE BEARS N73°31'30"W A DISTANCE OF 44.75'.

# 4110



SECTION CORNER FOR SECTIONS 19, 20, 29, & 30, T22N, R51E, MDM. FOUND 14"X10"X3" LIMESTONE, LAYING OVER, WITH 5 NOTCHES ON ONE FACE AND TWO NOTCHES ON ANOTHER FACE. ACCEPTED AS THE ORIGINAL MONUMENT. REMOVED STONE, AND IN THE STONE'S FOOTPRINT, SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH THE GROUND IN AN AREA WITH SAGEBRUSH, PINIONS, AND JUNIPERS. POINT IS APPROXIMATELY 40' EAST OF A NORTH/SOUTH RUNNING DIRT ROAD. PLACED ORIGINAL STONE .5' SOUTH OF OF CORNER AND SET T-POST 1' NORTH OF CORNER. FROM THIS CORNER A NOT-ACCEPTED UNMARKED STONE WITH OLD T-POST BEARS S9°18'10"W A DISTANCE OF 134.05'




QUARTER CORNER COMMON TO SECTION 29 AND SECTION 30, T22N, R51E, MDM. FOUND 4"X4"X3.25' WEATHERED WOOD POST LAYING ON THE GROUND IN A NE/SW DIRECTION. NO SUBSURFACE EVIDENCE OF WOOD POST WAS FOUND. ACCEPTED AS THE ORIGINAL MONUMENT HOLDING THE NORTHEAST END OF THE WOOD POST. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS 1" BELOW THE GROUND IN AN AREA OF LOW BRUSH. SET T-POST 1' NORTH OF CORNER.

### 4130


COMPUTED POINT NOTHING FOUND OR SET

QUARTER CORNER BETWEEN SECTION 25, T22N, R50E, MDM., AND SECTION 30, T22N, R51E, MDM. NO ORIGINAL EVIDENCE FOUND. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION ALONG THE RANGE LINE (FROM #4020 TO #4170). NOTHING SET. CORNER IS IN PREVIOUSLY CULTIVATED AREA.




SECTION CORNER FOR SECTIONS 25 & 36, T22N, R50E, MDM., AND SECTIONS 30 & 31, T22N, R51E, MDM. FOUND 4"X4"X3.25' AXE HEWN WOOD POST LAYING IN A NORTH/SOUTH DIRECTION. POST HAS VISIBLE, BUT ILLEGIBLE, SCRIBING ON ONE FACE. NO SUBSURFACE EVIDENCE OF WOOD POST WAS FOUND. ACCEPTED AS THE ORIGINAL MONUMENT HOLDING THE SOUTH END (THE END OPPOSITE THE SCRIBES) OF THE WOOD POST. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS 1" BELOW THE GROUND IN AN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER.

### 4180



QUARTER CORNER COMMON TO SECTION 30 AND SECTION 31, T22N, R51E, MDM. FOUND FIVE 5" LONG DETERIORATED WOOD POST REMNANTS LAYING IN A 6' DIAMETER AREA. NO SUBSURFACE EVIDENCE OF WOOD POST WAS FOUND. ACCEPTED AS THE ORIGINAL MONUMENT HOLDING THE LARGEST OF THE WOOD REMNANTS (MOST NORTHERLY). SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS 1" ABOVE THE GROUND IN AN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER.

### 4190




SECTION CORNER FOR SECTIONS 29, 30, 31, & 32, T22N, R51E, MDM. FOUND 2"X3"X3' DETERIORATED WOOD POST LAYING IN A NORTH/SOUTH DIRECTION. NO VISIBLE SCRIBING ON POST. NO SUBSURFACE EVIDENCE OF WOOD POST WAS FOUND. ACCEPTED AS THE ORIGINAL MONUMENT HOLDING THE SOUTH END OF THE WOOD POST. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS 1" BELOW THE GROUND. POINT IS APPROXIMATELY 25' WEST OF THE CENTERLINE OF THE MAIN ROAD LEADING TO ROBERTS CREEK RANCH AND IS APPROXIMATELY 3.5' EAST OF A SE/NW RUNNING BARBED WIRE FENCE. SET T-POST 1' NORTH OF CORNER.



CENTER QUARTER OF SECTION 24, T22N, R50E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER.

### 4230



EAST SIXTEENTH CORNER COMMON TO SECTION 13 AND SECTION 24, T22N, R50E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN AREA OF A DRY POND. SET T-POST 1' NORTH OF CORNER.

## RYAN G. COOK **EXPIRES** 1-17-2013

DOC # 0223718 Official Record Recording requested By SUMMIT ENGINEERING Eureka County - NV Mike Rebaleati - Recorder Page 2 of 3



### RECORD OF SURVEY

SECTION 24, T22N, R50E, MDM and SECTIONS 19 & 30, T22N, R51E, MDM ROBERTS CREEK RANCH


UREKA COUNTY




CENTER EAST SIXTEENTH CORNER OF SECTION 24, T22N, R50E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER.




CENTER QUARTER OF SECTION 19, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY EXTENDING THE BEARING OF THE EAST LINE OF THE SOUTHEAST QUARTER (#4110 TO #4040) FROM THE SOUTH QUARTER CORNER (#4100) TO INTERSECT THE EAST/WEST CENTERLINE OF THE SECTION (#4040 TO #4050). SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS 1" ABOVE THE GROUND IN AREA OF LOW BRUSH, JUNIPERS, & PINIONS. SET T-POST 1' NORTH OF




CENTER WEST SIXTEENTH CORNER OF SECTION 19, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH THE GROUND IN AREA OF LOW BRUSH, JUNIPERS, & PINIONS. SET T-POST 1' NORTH OF CORNER.




SOUTHWEST SIXTEENTH CORNER OF SECTION 19, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN PREVIOUSLY CULTIVATED AREA. SET T-POST 1' NORTH OF CORNER.



CENTER SOUTH SIXTEENTH CORNER OF SECTION 19, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS 1" ABOVE GROUND IN AREA OF LOW BRUSH, JUNIPERS, & PINIONS. SET T-POST 1' NORTH OF CORNER.




CENTER QUARTER OF SECTION 30, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER.




CENTER NORTH SIXTEENTH CORNER OF SECTION 30, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN PREVIOUSLY CULTIVATED AREA. SET T-POST 1' NORTH OF CORNER.

4310 SUMM I T ENG NW 1/16 • S30 21 PL 2012 S 15224

NORTHWEST SIXTEENTH CORNER OF SECTION 30, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN PREVIOUSLY CULTIVATED AREA. SET T-POST 1' NORTH OF CORNER.



CENTER WEST SIXTEENTH CORNER OF SECTION 30, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN PREVIOUSLY CULTIVATED AREA. SET T-POST 1' NORTH OF CORNER.



WEST SIXTEENTH CORNER COMMON TO SECTION 30 AND SECTION 31, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER.



THIS IS A GPS CONTINUOUSLY OPERATING REFERENCE STATION (CORS)

PER NGS DATA SHEET:
DESIGNATION: AUSTIN 1 CORS ARP
CORS ID: AST1
PID: DG7018

# COORDINATE TABLE

	NEVADA STATE PLANE EAST ZONE, NSRS 2011 SCALED BY 1.000362 U.S. SURVEY FEET		GEODETIC		NEVADA STATE PLANE EAST ZONE, NSRS 2011 METERS GRID COORDINATES	
- au = "	GROUND COO		N. LATITUDE	W. LONGITUDE	NORTHING	EASTING
POINT#	NORTHING	EASTING	39°44'35.38981"	116°16'27.71483"	8554326.558	140775.291
0001	28075479.360	462027.460	39°45'56.77594"	116°18'29.32998"	8556859.298	137900.292
4000	28083791.868	452591.654 455316.598	39°45'56.59554"	116°17'54.44209"	8556847.061	138730.556
4010	28083751.704	458041.542	39°45'56.41222"	116°17'19.55421"	8556834.823	139560.820
4020	28083711.540		39°45'30.39841"	116°16'13.97157"	8556020.449	141115.489
4040	28081038.747	463143.998	39°45'30.31029"	116°17'19.86646"	8556029.923	139547.049
4050	28081069.842	457996.344	39°45'30.49562"	116°18'29.04629"	8556048.783	137900.487
4060	28081131.741	452592.292	39°45'04.21526"	116°18'28.76271"	8555238.268	137900.681
4070	28078471.614	452592.930	39°45'04.21320"	116°17'54.47071"	8555231.646	138716.979
4080	28078449.879	455272.038	39°45'04.20832"	116°17'20.17868"	8555225.023	139533.277
4090	28078428.144	457951.146	39°45'04.23586"	116°16'46.91689"	8555219.678	140325.059
4100	28078410.600	460549.790	39°45'04.16819"	116°16'13.91225"	8555211.525	141110.696
4110	28078383.842	463128.268	39°44'37.76698"	116°16'13.80100"	8554397.319	141107.101
4120	28075711.602	463116.467 457905.948	39°44'38.10632"	116°17'20.49089"	8554420.123	139519.506
4130	28075786.445	457905.946 457860.750	39°44'12.00429"	116°17'20.80306"	8553615.224	139505.735
4170	28073144.747		39°44'11.93600"	116°16'47.03942"	8553606.829	140309.608
4180	28073117.196	460499.079	39°44'11.77426"	116°16'13.63611"	8553595.703	141104.880
4190	28073080.679	463109.179	39°45'30.40439"	116°17'54.45638"	8556039.353	138723.768
4220	28081100.791	455294.318 456679.070	39°45'56.50425"	116°17'36.99815"	8556840.942	139145.688
4230	28083731.622		39°45'30.35769"	116°17'37.16142"	8556034.638	139135.408
4240	28081085.317	456645.331	39°45'30.35557"	116°16'46.97942"	8556025.195	140329.832
4250	28081054.323	460565.454	39°45'30.33323"	116°17'03.58857"	8556027.589	139934.498
4260	28081062.181	459267.961	39°45'17.27766"	116°17'03.65218"	8555624.980	139929.833
4270	28079740.810	459252.651	39°45'17.29572"	116°16'46.94815"	8555622.436	140327.445
4280	28079732.461	460557.622	39°44'37.93713"	116°16'46.97849"	8554408.664	140317.290
4290	28075748.836	460524.290	39°44'51.08650"	116°16'46.94769"	8554814.171	140321.174
4300	28077079.718	460537.040	39°44'51.12264"	116°17'03.82595"	8554818.419	139919.386
4310	28077093.659	459218.363	39°44'38.02308"	116°17'03.93609"	8554414.463	139913.603
4320	28075767.867	459199.384	39°44'11.97096"	116°17'04.15663"	8553611.085	139902.067
4330	28073131.164	459161.521	39°23'24.92475"	117°18'30.07426"	8516339.961	51402.458
9143	27950806.553	168703.945	39 23 24.92473	111 10 00.01 720	1 001000000	



DOC # 0223718

Official Record

Recording requested By SUMMIT ENGINEERING

Eureka County - NV

Mike Rebaleati - Recorder

Fee: Page 3 of Recorder By FES

RPTT: Recorded By FES

Book- Page- 0000




RECORD OF SURVEY
OF
SECTION 24, T22N, R50E, MDM and
SECTIONS 19 & 30, T22N, R51E, MDM

ROBERTS CREEK RANCH




Robert Creek Kand Reerd & Lumey


# MONUMENT DESCRIPTIONS




CENTER EAST SIXTEENTH CORNER OF SECTION 24, T22N, R50E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER.




CENTER QUARTER OF SECTION 19, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY EXTENDING THE BEARING OF THE EAST LINE OF THE SOUTHEAST QUARTER (#4110 TO #4040) FROM THE SOUTH QUARTER CORNER (#4100) TO INTERSECT THE EAST/WEST CENTERLINE OF THE SECTION (#4040 TO #4050). SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS 1" ABOVE THE GROUND IN AREA OF LOW BRUSH, JUNIPERS, & PINIONS. SET T-POST 1' NORTH OF CORNER.




CENTER WEST SIXTEENTH CORNER OF SECTION 19, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH THE GROUND IN AREA OF LOW BRUSH, JUNIPERS, & PINIONS. SET T-POST 1' NORTH OF CORNER.




SOUTHWEST SIXTEENTH CORNER OF SECTION 19, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN PREVIOUSLY CULTIVATED AREA. SET T-POST 1' NORTH OF CORNER.



CENTER SOUTH SIXTEENTH CORNER OF SECTION 19, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS 1" ABOVE GROUND IN AREA OF LOW BRUSH, JUNIPERS, & PINIONS. SET T-POST 1' NORTH OF CORNER.




CENTER QUARTER OF SECTION 30, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER.




CENTER NORTH SIXTEENTH CORNER OF SECTION 30, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN PREVIOUSLY CULTIVATED AREA. SET T-POST 1' NORTH OF CORNER.

# 4310 Synth I T ENG NW 1/16 • S30

NORTHWEST SIXTEENTH CORNER OF SECTION 30, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY BREAKDOWN OF THE SECTION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN PREVIOUSLY CULTIVATED AREA. SET T-POST 1' NORTH OF CORNER.



CENTER WEST SIXTEENTH CORNER OF SECTION 30, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN PREVIOUSLY CULTIVATED AREA. SET T-POST 1' NORTH OF CORNER.



WEST SIXTEENTH CORNER COMMON TO SECTION 30 AND SECTION 31, T22N, R51E, MDM. NOTHING FOUND. ESTABLISHED BY SINGLE PROPORTIONATE MEASUREMENT COMPUTATION. SET 5/8" REBAR WITH 2" DIAMETER ALUMINUM CAP WITH MARKINGS AS SHOWN TO THE LEFT. TOP OF CAP IS FLUSH WITH GROUND IN AREA OF LOW SAGE. SET T-POST 1' NORTH OF CORNER.



THIS IS A GPS CONTINUOUSLY OPERATING REFERENCE STATION (CORS) PER NGS DATA SHEET:

DESIGNATION: AUSTIN 1 CORS ARP

CORS ID: AST1

PID: DG7018

# COORDINATE TABLE

NEVADA STATE PLANE EAST ZONE, NSRS 2011 SCALED BY 1.000362 U.S. SURVEY FEET				NEVADA STATE PLANE EAST ZONE, NSRS 2011 METERS	
GROUND COO		GEODETIC		GRID COORDINATES	
NORTHING	EASTING	N. LATITUDE	W. LONGITUDE	NORTHING	EASTING
28075479.360	462027.460	39°44'35.38981"	116°16'27.71483"	8554326.558	140775.291
28083791.868	452591.654	39°45'56.77594"	116°18'29.32998"	8556859.298	137900.292
28083751.704	455316.598	39°45'56.59554"	116°17'54.44209"	8556847.061	138730.556
28083711.540	458041.542	39°45'56.41222"	116°17'19.55421"	8556834.823	139560.820
28081038.747	463143.998	39°45'30.39841"	116°16'13.97157"	8556020.449	141115.489
28081069.842	457996.344	39°45'30.31029"	116°17'19.86646"	8556029.923	139547.049
28081131.741	452592.292	39°45'30.49562"	116°18'29.04629"	8556048.783	137900.487
28078471.614	452592.930	39°45'04.21526"	116°18'28.76271"	8555238.268	137900.681
28078449.879	455272.038	39°45'04.21320"	116°17'54.47071"	8555231.646	138716.979
28078428.144	457951.146	39°45'04.20832"	116°17'20.17868"	8555225.023	139533.277
28078410.600	460549.790	39°45'04.23586"	116°16'46.91689"	8555219.678	140325.059
28078383.842	463128.268	39°45'04.16819"	116°16'13.91225"	8555211.525	141110.696
28075711.602	463116.467	39°44'37.76698"	116°16'13.80100"	8554397.319	141107.101
28075786.445	457905.948	39°44'38.10632"	116°17'20.49089"	8554420.123	139519.506
28073144.747	457860.750	39°44'12.00429"	116°17'20.80306"	8553615.224	139505.735
28073117.196	460499.079	39°44'11.93600"	116°16'47.03942"	8553606.829	140309.608
28073080.679	463109.179	39°44'11.77426"	116°16'13.63611"	8553595.703	141104.880
28081100.791	455294.318	39°45'30.40439"	116°17'54.45638"	8556039.353	138723.768
28083731.622	456679.070	39°45'56.50425"	116°17'36.99815"	8556840.942	139145.688
28081085.317	456645.331	39°45'30.35769"	116°17'37.16142"	8556034.638	139135.408
28081054.323	460565.454	39°45'30.35557"	116°16'46.97942"	8556025.195	140329.832
28081062.181	459267.961	39°45'30.33323"	116°17'03.58857"	8556027.589	139934.498
28079740.810	459252.651	39°45'17.27766"	116°17'03.65218"	8555624.980	139929.833
28079732.461	460557.622	39°45'17.29572"	116°16'46.94815"	8555622.436	140327.445
28075748.836	460524.290	39°44'37.93713"	116°16'46.97849"	8554408.664	140317.290
28077079.718	460537.040	39°44'51.08650"	116°16'46.94769"	8554814.171	140321.174
28077079.718	459218.363	39°44'51.12264"	116°17'03.82595"	8554818.419	139919.386
		39°44'38.02308"	116°17'03.93609"	8554414.463	139913.603
					139902.067
					51402.458
	28075767.867 28073131.164 27950806.553	28073131.164 459161.521	28073131.164 459161.521 39°44'11.97096"	28073131.164 459161.521 39°44'11.97096" 116°17'04.15663"	28073131.164 459161.521 39°44'11.97096" 116°17'04.15663" 8553611.085



DOC # 0223718

Official Record
Recording requested By
SUMMIT ENGINEERING

Eureka County - NV
Mike Rebaleati - Recorder
Fee: Page 3 of 3
RRTI - Recorded By: FES



SECTION 24, T22N, R50E, MDM and SECTIONS 19 & 30, T22N, R51E, MDM

ROBERTS CREEK RANCH

DREKA COUNTY

\[
\text{DWGS\J29648\_RobertsCreekRanch\RCR\_ROS.DWG} \simplify 9: 52 \text{ AM \* 17-JAN-2013} \]

\[
\text{SHEET} \]

\[
\text{SHEET} \]

\[
\text{3} \]

OF

\[
\text{5405 MAE ANNE AVENUE, RENO, NV. 89523} \\
\text{PHONE: (775) 747-8559} \]

\[
\text{3} \]